


MAGS 3" SPOT

MAGS Series 3 in Spot Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be moved easily as desired. MAGS-D03 is a DRY rated Magnetic Track, MicroSpot Aluminum light offered in a black or white finish. This Light Fixture is CETL listed and contains 3 lights, total of 4 watts and delivers 240 lumens. Offered in choice of 12, 34, or 48 degree beam spreads and choice of 2700K, 3000K, 3500K, or 4000K CCT. Osram LED module with >90 CRI. Dimmable via 24V remote driver needed.



Model Number Configuration

D03

Optics**CCT****Finish** D12 - 20° 27 - 2700K BL - Black D34 - 34° 30 - 3000K WH - White D48 - 48° 35 - 3500K 40 - 4000K

Electrical

Voltage	24V
Dimming	Driver dependent
Power	4W
Lumens	240
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598


Mechanical

Installation	Fixture engages with track system electrically and mechanically via magnetic connection and can be moved easily as desired.
Cord Length	N/A
Dimensions	3.25" L x 1.375" x 2.125" H
Weight	.5 lbs
Material	Aluminum
Finish	Powder Coated


Driver Options

Driver code	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--


Photometric and Light Distribution

D12

h(m)	E(lx)	Φ(m)
1	3782	Φ0.21
2	945	Φ0.43
3	420	Φ0.64
4	236	Φ0.86
5	151	Φ1.07

D34

h(m)	E(lx)	Φ(m)
1	1072	Φ0.58
2	268	Φ1.16
3	119	Φ1.75
4	67	Φ2.33
5	42	Φ2.92

D48

h(m)	E(lx)	Φ(m)
1	662	Φ0.82
2	165	Φ1.65
3	73	Φ2.47
4	41	Φ3.30
5	26	Φ4.13