


# MAGS 3" SPOT

MAGS Series 3 in Spot Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be moved easily as desired. MAGS-D03 is a DRY rated Magnetic Track, MicroSpot Aluminum light offered in a black or white finish. This Light Fixture is CETL listed and contains 3 lights, total of 4 watts and delivers 240 lumens. Offered in choice of 12, 34, or 48 degree beam spreads and choice of 2700K, 3000K, 3500K, or 4000K CCT. Osram LED module with >90 CRI. Dimmable via 24V remote driver needed.



## Model Number Configuration

**D03**

---

**Optics**

- D12 - 20°
- D34 - 34°
- D48 - 48°

--

**CCT**

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

--

**Finish**

- BL - Black
- WH - White

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	4W
<b>Lumens</b>	240
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	Fixture engages with track system electrically and mechanically via magnetic connection and can be moved easily as desired.
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	3.25" L x 1.375" x 2.125" H
<b>Weight</b>	.5 lbs
<b>Material</b>	Aluminum
<b>Finish</b>	Powder Coated

## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

**Photometric and Light Distribution**

<b>D12</b>		<b>D34</b>																																							
<b>12°</b>		<table border="1"> <thead> <tr> <th>h(m)</th> <th>E(lx)</th> <th>Φ(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>3782</td><td>Φ0.21</td></tr> <tr><td>2</td><td>945</td><td>Φ0.43</td></tr> <tr><td>3</td><td>420</td><td>Φ0.64</td></tr> <tr><td>4</td><td>236</td><td>Φ0.86</td></tr> <tr><td>5</td><td>151</td><td>Φ1.07</td></tr> </tbody> </table>	h(m)	E(lx)	Φ(m)	1	3782	Φ0.21	2	945	Φ0.43	3	420	Φ0.64	4	236	Φ0.86	5	151	Φ1.07	<b>34°</b>		<table border="1"> <thead> <tr> <th>h(m)</th> <th>E(lx)</th> <th>Φ(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>1072</td><td>Φ0.58</td></tr> <tr><td>2</td><td>268</td><td>Φ1.16</td></tr> <tr><td>3</td><td>119</td><td>Φ1.75</td></tr> <tr><td>4</td><td>67</td><td>Φ2.33</td></tr> <tr><td>5</td><td>42</td><td>Φ2.92</td></tr> </tbody> </table>	h(m)	E(lx)	Φ(m)	1	1072	Φ0.58	2	268	Φ1.16	3	119	Φ1.75	4	67	Φ2.33	5	42	Φ2.92
h(m)	E(lx)	Φ(m)																																							
1	3782	Φ0.21																																							
2	945	Φ0.43																																							
3	420	Φ0.64																																							
4	236	Φ0.86																																							
5	151	Φ1.07																																							
h(m)	E(lx)	Φ(m)																																							
1	1072	Φ0.58																																							
2	268	Φ1.16																																							
3	119	Φ1.75																																							
4	67	Φ2.33																																							
5	42	Φ2.92																																							
<b>D48</b>																																									
<b>48°</b>		<table border="1"> <thead> <tr> <th>h(m)</th> <th>E(lx)</th> <th>Φ(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>662</td><td>Φ0.82</td></tr> <tr><td>2</td><td>165</td><td>Φ1.65</td></tr> <tr><td>3</td><td>73</td><td>Φ2.47</td></tr> <tr><td>4</td><td>41</td><td>Φ3.30</td></tr> <tr><td>5</td><td>26</td><td>Φ4.13</td></tr> </tbody> </table>	h(m)	E(lx)	Φ(m)	1	662	Φ0.82	2	165	Φ1.65	3	73	Φ2.47	4	41	Φ3.30	5	26	Φ4.13																					
h(m)	E(lx)	Φ(m)																																							
1	662	Φ0.82																																							
2	165	Φ1.65																																							
3	73	Φ2.47																																							
4	41	Φ3.30																																							
5	26	Φ4.13																																							