


MAGS 6" FOLD ADJUSTABLE SPOT

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be moved easily along the track. Model MAGS-F06 is a DRY rated Magnetic Track, 90 Deg Foldable MicroSpot Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and contains 6 lights, using a total of 8 watts., Downlight delivering 520 lumens using a Osram LEDModule with >90 CRI. Choose 12, 34, or 48-degree beam spreads, and choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver (sold separately). Fixture Dimensions are 7.125 inches tall x 6.375 inches wide x 1.375 inches deep.



Model Number Configuration

F06

Optics

- D12 - 20°
- D34 - 34°
- D48 - 48°

--

CCT

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

--

Finish

- BL - Black
- WH - White

Electrical

Voltage	24V
Dimming	Driver dependent
Power	8W
Lumens	520
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598




Mechanical

Installation	N/A
Cord Legth	N/A
Dimensions	6.375"L x 1.375"W x 7.125"H
Weight	2.07 lbs
Material	Aluminum
Finish	Powder Coated

Driver Options

Driver code	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

Photometric and Light Distribution

D12				D34			
12°				34°			
							
	h(m)	E(lx)	Φ(m)		h(m)	E(lx)	Φ(m)
	1	5723	Φ0.21		1	1807	Φ0.63
	2	1431	Φ0.42		2	451	Φ1.26
	3	635	Φ0.63		3	200	Φ1.89
	4	357	Φ0.84		4	112	Φ2.52
	5	228	Φ1.05		5	72	Φ3.15
D48							
48°							
							
	h(m)	E(lx)	Φ(m)				
	1	1287	Φ0.79				
	2	321	Φ1.58				
	3	143	Φ2.37				
	4	80	Φ3.16				
	5	51	Φ3.95				