


# MAGS 6" GLOBE

MAGS Series Light Fixture. The fixture engages with the track system electrically and mechanically via a magnetic connection and can be easily moved along the track. Model MAGS-GD is a DRY rated Magnetic Track, Glass Globe Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 5 watts, Diffuse Lens delivering 680 lumens using an Osram LEDModule with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000k CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 8.5 inches tall x 6.375 inches wide x 5.875 inches deep.



## Model Number Configuration

GD	---	--	--
	Optics	CCT	Finish
	<input type="checkbox"/> DIF - Diffuse	<input type="checkbox"/> 27 - 2700K	<input type="checkbox"/> BL - Black
		<input type="checkbox"/> 30 - 3000K	<input type="checkbox"/> WH - White
		<input type="checkbox"/> 35 - 3500K	
		<input type="checkbox"/> 40 - 4000K	

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	5W
<b>Lumens</b>	680
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	6.375"L x 5.875"W x 8.5"H
<b>Weight</b>	1.37 lbs
<b>Material</b>	Aluminum and glass
<b>Finish</b>	Powder Coated

## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	----------------------------------------------------------------------------------------------------------------------------------------------

**Photometric and Light Distribution**

