


MAGS 6" DIFFUSED LINEAR

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-L16 is a DRY rated Magnetic Track, Linear Lensed Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 8 watts, Diffuse Lens delivering 420 lumens using a Osram LEDModule with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 2.125 inches tall x 6.375 inches wide x 1.375 inches deep.





Model Number Configuration

L16			
	Optics	CCT	Finish
	□ DIF - Diffuse	□ 27 - 2700K □ 30 - 3000K □ 35 - 3500K □ 40 - 4000K	□ BL - Black □ WH - White



PROJECT NAME: FIXTURE TYPE:

Product sheet printed on: 2025-08-02 20:24:39

Electrical

Voltage 24V

Dimming Driver dependent

 Power
 8W

 Lumens
 420

 Power factor
 N/A

Environmental

CRI >90
Environment Dry
Light Source LED
Chip Osram
Life rating N/A

Listings C-ETL Listed to UL1598

Mechanical

Dimensions 7.5"L x 1.375"W x 2.125"H

Weight .68 lbs

Material Aluminum and polycarbonate


Finish Powder Coated

Driver Options

Driver code PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100%

dimming. Up to 20 Small or 10 Large Pendants.







Photometric and Light Distribution

