


PROJECT NAME: FIXTURE TYPE: Product sheet printed on: **2025-08-31 23:29:14**

MAGS 6" DIFFUSED LINEAR

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-L16 is a DRY rated Magnetic Track, Linear Lensed Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 8 watts, Diffuse Lens delivering 420 lumens using a Osram LEDModule with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 2.125 inches tall x 6.375 inches wide x 1.375 inches deep.





Model Number Configuration

L16			
	Optics	ССТ	Finish
	☐ DIF - Diffuse	□ 27 - 2700K □ 30 - 3000K □ 35 - 3500K □ 40 - 4000K	□ BL - Black □ WH - White

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2024 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.



Electrical

Voltage	24V
Dimming	Driver dependent
Power	8W
Lumens	420
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598

Mechanical

Installation	N/A
Cord Legth	N/A
Dimensions	7.5"L x 1.375"W x 2.125"H
Weight	.68 lbs
Material	Aluminum and polycarbonate
Finish	Powder Coated

Driver Options

Driver code PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.



Photometric and Light Distribution

