


# MAGS Ø3.6" SPOT

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-S92R is a DRY rated Magnetic Track, Adjustable Spotlight Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and contains 1 lights, total of 15 watts, delivering 820 lumens using a Osram LEDModule with +90 CRI. Dimmable via 24V Volt Remote Driver (sold separately). Choice of 10, 20, or 30 degree beam spread. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Spotlight Dimensions are 7.125 inches long x 5.5 inches diameter with a 90 degree tilt and 360 degree rotation.



## Model Number Configuration

**S92R**

---

**Optics**

- D10 - 10°
- D20 - 20°
- D30 - 30°

--

**CCT**

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

--

**Finish**

- BL - Black
- WH - White

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	15W
<b>Lumens</b>	820
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	7.125"L x 5.5" diameter with a 90 degree tilt and 360 degree rotation.
<b>Weight</b>	1.37 lbs
<b>Material</b>	Aluminum
<b>Finish</b>	Powder Coated

## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

## Photometric and Light Distribution

D10				D20			
<b>10°</b> 	h(m)	E(lx)	Φ(m)	<b>20°</b> 	h(m)	E(lx)	Φ(m)
	1	9750	Φ0.20		1	6022	Φ0.25
	2	2437	Φ0.40		2	1505	Φ0.50
	3	1083	Φ0.60		3	669	Φ0.75
	4	609	Φ0.80		4	376	Φ1.00
	5	390	Φ1.00		5	240	Φ1.25
<b>D30</b>							
<b>30°</b> 	h(m)	E(lx)	Φ(m)				
	1	2204	Φ0.39				
	2	551	Φ0.79				
	3	244	Φ1.19				
	4	137	Φ1.59				
	5	88	Φ1.99				