


MAGS 5.4" WALL WASH

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-W13 is a DRY rated Magnetic Track, Wall Washer Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and uses a total of 8 watts, Wall Wash Lens delivering 400 lumens using a Osram LEDModule with +90 CRI. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Remote Driver (sold separately). Fixture Dimensions are 2.125 inches tall x 5.375 inches wide x 1.375 inches deep.



Model Number Configuration

W13

Optics

WW - Wall Wash

--

CCT

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

--

Finish

- BL - Black
- WH - White

Electrical

| | |
|---------------------|------------------|
| Voltage | 24V |
| Dimming | Driver dependent |
| Power | 8W |
| Lumens | 400 |
| Power factor | N/A |

Environmental

| | |
|---------------------|------------------------|
| CRI | >90 |
| Environment | Dry |
| Light Source | LED |
| Chip | Osram |
| Life rating | N/A |
| Listings | C-ETL Listed to UL1598 |

Mechanical

| | |
|---------------------|--------------------------------|
| Installation | N/A |
| Cord Legth | N/A |
| Dimensions | 5.375" L x 1.375" W x 2.125" H |
| Weight | .71 lbs |
| Material | Aluminum |
| Finish | Powder Coated |


Driver Options

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Driver code | PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants. |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------|

Photometric and Light Distribution

W13

Wallwasher



| h(m) | E(lx) | Φ(m) |
|------|-------|-------|
| 1 | 324 | Φ0.84 |
| 2 | 81 | Φ1.68 |
| 3 | 36 | Φ2.52 |
| 4 | 20 | Φ3.36 |
| 5 | 12 | Φ4.20 |