


MAGS 1" SPOT

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-D0301 is a DRY rated Magnetic Track, MicroSpot Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and uses a total of 2 watts, delivering 126 lumens using a Osram 2700K LEDModule with >90 CRI. Choose 12, 34, or 48-degree beam spreads, and choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver (sold separately). Fixture Dimensions are 2.125 inches tall x 1.375 inches wide x 1.375 inches deep.



Model Number Configuration

D0301

Optics

- D12 - 12°
- D34 - 34°
- D48 - 48°

CCT

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

Finish

- BL - Black
- WH - White

Electrical

Voltage	24V
Dimming	Driver dependent
Power	2
Lumens	126
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598




Mechanical

Installation	N/A
Cord Legth	N/A
Dimensions	1.375" L x 1.375" W x 2.125"H
Weight	N/A
Material	Aluminum
Finish	Powder Coated

Driver Options

Driver code	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

Photometric and Light Distribution

D12				D34						
12°		h(m)	E(lx)	Φ(m)	34°		h(m)	E(lx)	Φ(m)	
		1	273	Φ0.40			1	278	Φ0.72	
		2	68	Φ0.81			2	69	Φ1.44	
		3	30	Φ1.22			3	30	Φ2.16	
		4	17	Φ1.63			4	17	Φ2.88	
		5	10	Φ2.04			5	11	Φ3.60	
D48										
48°		h(m)	E(lx)	Φ(m)						
		1	223	Φ0.67						
		2	55	Φ1.35						
		3	24	Φ2.03						
		4	13	Φ2.71						
		5	8	Φ3.39						