



# MAGS 1" SPOT

MAGS Series Light Fixture. Fixture engages with track system electrically and mechanically via magnetic connection and can be easily moved along the track. Model MAGS-D0301 is a DRY rated Magnetic Track, MicroSpot Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and uses a total of 2 watts, delivering 126 lumens using a Osram 2700K LEDModule with >90 CRI. Choose 12, 34, or 48-degree beam spreads, and choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver (sold separately). Fixture Dimensions are 2.125 inches tall x 1.375 inches wide x 1.375 inches deep.



## Model Number Configuration

**D0301**

---

---

---

**Optics****CCT****Finish** D12 - 12° 27 - 2700K BL - Black D34 - 34° 30 - 3000K WH - White D48 - 48° 35 - 3500K 40 - 4000K

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	2
<b>Lumens</b>	126
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598


## Mechanical

<b>Installation</b>	N/A
<b>Cord Length</b>	N/A
<b>Dimensions</b>	1.375" L x 1.375" W x 2.125"H
<b>Weight</b>	N/A
<b>Material</b>	Aluminum
<b>Finish</b>	Powder Coated


## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--


## Photometric and Light Distribution

**D12****12°**

$h(m)$	$E(lx)$	$\Phi(m)$
1	273	$\Phi 0.40$
2	68	$\Phi 0.81$
3	30	$\Phi 1.22$
4	17	$\Phi 1.63$
5	10	$\Phi 2.04$

**D34****34°**

$h(m)$	$E(lx)$	$\Phi(m)$
1	278	$\Phi 0.72$
2	69	$\Phi 1.44$
3	30	$\Phi 2.16$
4	17	$\Phi 2.88$
5	11	$\Phi 3.60$

**D48****48°**

$h(m)$	$E(lx)$	$\Phi(m)$
1	223	$\Phi 0.67$
2	55	$\Phi 1.35$
3	24	$\Phi 2.03$
4	13	$\Phi 2.71$
5	8	$\Phi 3.39$