

# DECO Ø1.4" PENDANT

Decorative 1.37" diameter pendant featuring a minimal design with top metal cylinder and bottom acrylic diffuser. Diffuser offered in a choice of five lengths. Top metal cylinder is 10" (250mm), and acrylic diffuser lengths are 2"(12" oah), 6" (16" oah), 12" ( 22" oah), 18" (28" oah), and 24" (34" oah). Powder-coated metal finish offered in black or white. Includes 4" octagonal junction box cover plate in matching metal finish. Fixture provided with field-adjustable 48" (1200mm) black cable standard. 5W Osram led module with 350 lumens delivered from pendant before acrylic diffuser. 90+CRI, L70/50K Hours. 20 degree beam angle. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dry Rated, ETL / cETL Listed. 24VDC remote driver required, sold separately.



## Model Number Configuration

**P35R** --

**Acrylic Length**

- 02 - 2" Acrylic (12" oah)
- 06 - 6" Acrylic (16" oah)
- 12 - 12" Acrylic (22" oah)
- 18 - 18" Acrylic (28" oah)
- 24 - 24" Acrylic (34" oah)

--

**CCT**

- 27 - 2700K
- 30 - 3000K
- 35 - 3500K
- 40 - 4000K

--

**Finish**

- BL - Black
- WH - White

## **Electrical**

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	5W
<b>Lumens</b>	350
<b>Power factor</b>	N/A

## **Environmental**

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## **Mechanical**

<b>Installation</b>	N/A
<b>Cord Length</b>	4' Standard Cord Length. Field Adjustable to shorter lengths. Longer Cord Length option available upon request.
<b>Dimensions</b>	1.37" Diameter x Overall heights: 12", 16", 22", 28 " or 34"
<b>Weight</b>	N/A
<b>Material</b>	Aluminum and acrylic
<b>Finish</b>	Powder Coated

## **Driver Options**

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--