

Product sheet printed on: 2025-08-02 20:20:30

DECO Ø2" PENDANT

Decorative 2" diameter pendant featuring a minimal design with top metal cylinder and bottom acrylic diffuser. Diffuser offered in a choice of five lengths. Top metal cylinder is 10" (250mm), and acrylic diffuser lengths are 2"(12" oah), 6" (16" oah), 12" (22" oah), 18" (28" oah), and 24" (34" oah). Powder-coated metal finish offered in black or white. Includes 4" octagonal junction box cover plate in matching metal finish. Fixture provided with field-adjustable 48" (1200mm) black cable standard. 10W Osram led module with 692 lumens delivered from pendant prior to acrylic diffuser. 90+CRI, L70/50K Hours. 20 degree beam angle. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dry Rated, ETL / cETL Listed. 24VDC remote driver required, sold separately.

Model Number Configuration

P50R			
	Acrylic Length	CCT	Finish
	☐ 02 - 2" Acrylic (12" oah)	☐ 27 - 2700K	☐ BL - Black
	☐ 06 - 6" Acrylic (16" oah)	□ 30 - 3000K	☐ WH - White
	☐ 12 - 12" Acrylic (22" oah)	☐ 35 - 3500K	
	☐ 18 - 18" Acrylic (28" oah)	☐ 40 - 4000K	
	☐ 24 - 24" Acrylic (34" oah)		



PROJECT NAME: FIXTURE TYPE:

Product sheet printed on: 2025-08-02 20:20:30

Electrical

Voltage 24V

Dimming Driver dependent

 Power
 10W

 Lumens
 692

 Power factor
 N/A

Environmental

CRI >90
Environment Dry
Light Source LED
Chip Osram
Life rating N/A

Listings C-ETL Listed to UL1598

Mechanical

Installation N/A

Cord Legth 4' Standard Cord Length. Field Adjustable to shorter lengths. Longer Cord Length option available upon

request

Dimensions 2" Diameter x Overall heights: 12", 16", 22", 28 " or 34"

Weight N/A

Material Aluminum and acrylic

Finish Powder Coated

Driver Options

Driver code PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100%

dimming. Up to 20 Small or 10 Large Pendants.