
FORMAE

PROJECT NAME: FIXTURE TYPE: Product sheet printed on: **2025-08-31 21:20:56**

MAGS 2" SQUARE SPOTLIGHT

MAGS Series Magnetic Track, Adjustable Square Spotlight Light Fixture. Choice of black or white finish. CETL listed. 8.25 inches long x 2inch square. 90 degree tilt; 360 degree rotation. 1 Light, 10 watt, Osram LED delivering 870 lumens. +90 CRI. Choice of 18, 24, or 36 degree beam spreads. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver, sold separately.





Model Number Configuration



LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2024 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.



Electrical

Voltage	N/A
Dimming	Driver dependent
Power	10W
Lumens	870
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	N/A
Life rating	N/A
Listings	C-ETL Listed to UL1598

Mechanical

Installation	N/A
Cord Legth	N/A
Dimensions	8.25" L x 2inch Square
Weight	N/A
Material	Aluminum
Finish	Powder Coated


Driver Options

Driver codePS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100%
dimming. Up to 20 Small or 10 Large Pendants.|PS-60-ELV - 60W, 24V Power Supply. 120V Only with
ELV Dimming to 10%. Fits in 4x4 Rectangular Junction Box.



D24

Photometric and Light Distribution




h(m)	E(Ix)	Φ(m)
1	4902	Ф0.32
2	1226	Φ0.65
3	544	Ф0.98
4	306	Φ1.31
5	196	Ф1.63

24°

h(m)	E(lx)	Φ(m)
1	4186	Ф0.39
2	1047	Ф0.79
3	465	Φ1.19
4	261	Φ1.58
5	167	Φ1.98

D36



h(m)	E(lx)	Φ(m)
1	2077	Ф0.64
2	519	Ф1.29
3	230	Ф1.94
4	129	Φ2.58
5	83	Ф3.23