


MAGS MINI 12" SPOT LINEAR

MAGS Mini Series Light Fixture. The fixture engages with the track system electrically and mechanically via a magnetic connection and can be moved easily along the track. Model MAGS-ES-D12 is a DRY rated Magnetic Track, MicroSpot Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and contains 12 lights, uses a total of 12 watts. Downlight delivering 1015 lumens using an Osram LED Module with >90 CRI. Choose 20, 34, or 48-degree beam spreads, and choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver (sold separately). Fixture Dimensions are 12 inches long x .89 inches wide x .73 inches deep.



Model Number Configuration

MAGS-ES-D12			
	---	--	--
	Optics	CCT	Finish
	☐ D12 - 20°	☐ 27 - 2700K	☐ BL - Black
	☐ D34 - 34°	☐ 30 - 3000K	☐ WH - White
	☐ D48 - 48°	☐ 35 - 3500K	
		☐ 40 - 4000K	

Electrical

Voltage	24V
Dimming	Driver dependent
Power	12W
Lumens	1015
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598


Mechanical


Installation	N/A
Cord Legth	N/A
Dimensions	12" L x .89" W x .73"D
Weight	N/A
Material	Aluminum
Finish	Powder Coated


Driver Options

Driver code	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
-------------	--

Photometric and Light Distribution

D12			
12° 	h(m)	E(lx)	Φ(m)
	1	11430	Φ0.21
	2	2857	Φ0.42
	3	1270	Φ0.63
	4	714	Φ0.85
	5	457	Φ1.06

D34			
34° 	h(m)	E(lx)	Φ(m)
	1	3545	Φ0.62
	2	886	Φ1.25
	3	393	Φ1.88
	4	221	Φ2.51
	5	141	Φ3.14

D48			
48° 	h(m)	E(lx)	Φ(m)
	1	2773	Φ0.79
	2	693	Φ1.58
	3	308	Φ2.37
	4	173	Φ3.16
	5	110	Φ3.95