


MAGS MINI 12" DIFFUSED LINEAR

MAGS Mini Series Light Fixture. The fixture engages with the track system electrically and mechanically via a magnetic connection and can be easily moved along the track. Model MAGS-ES-L30 is a DRY rated Magnetic Track, Linear Lensed Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 6 watts, Diffuse Lens delivering 435 lumens using a Osram LED Module with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 12 inches L x .89 inches W x .73 inches Deep



Model Number Configuration

MAGS-ES-L30

Optics

DIF - Diffuse

--

CCT

27 - 2700K

30 - 3000K

35 - 3500K

40 - 4000K

--

Finish

BL - Black

WH - White

Electrical

| | |
|---------------------|------------------|
| Voltage | 24V |
| Dimming | Driver dependent |
| Power | 6W |
| Lumens | 435 |
| Power factor | N/A |

Environmental

| | |
|---------------------|------------------------|
| CRI | >90 |
| Environment | Dry |
| Light Source | LED |
| Chip | Osram |
| Life rating | N/A |
| Listings | C-ETL Listed to UL1598 |

Mechanical

| | |
|---------------------|--|
| Installation | N/A |
| Cord Legth | N/A |
| Dimensions | 12 inches L x .89 inches W x .73 inches Deep |
| Weight | N/A |
| Material | Aluminum and acrylic |
| Finish | Powder Coated |


Driver Options

| | |
|--------------------|--|
| Driver code | PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants. |
|--------------------|--|

Photometric and Light Distribution

DIF

Diffuse



| h(m) | E(lx) | Φ(m) |
|------|-------|--------|
| 1 | 168 | Φ2.44 |
| 2 | 42 | Φ4.88 |
| 3 | 18 | Φ7.32 |
| 4 | 10 | Φ9.76 |
| 5 | 6 | Φ12.20 |