


# MAGS MINI 12" DIFFUSED LINEAR

MAGS Mini Series Light Fixture. The fixture engages with the track system electrically and mechanically via a magnetic connection and can be easily moved along the track. Model MAGS-ES-L30 is a DRY rated Magnetic Track, Linear Lensed Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 6 watts, Diffuse Lens delivering 435 lumens using a Osram LED Module with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 12 inches L x .89 inches W x .73 inches Deep



## Model Number Configuration

### MAGS-ES-L30

---

#### Optics

DIF - Diffuse

--

#### CCT

27 - 2700K

30 - 3000K

35 - 3500K

40 - 4000K

--

#### Finish

BL - Black

WH - White

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	6W
<b>Lumens</b>	435
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Osram
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	12 inches L x .89 inches W x .73 inches Deep
<b>Weight</b>	N/A
<b>Material</b>	Aluminum and acrylic
<b>Finish</b>	Powder Coated


## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

**Photometric and Light Distribution**

**DIF**

**Diffuse**



h(m)	E(lx)	Φ(m)
1	168	Φ2.44
2	42	Φ4.88
3	18	Φ7.32
4	10	Φ9.76
5	6	Φ12.20