


MAGS MINI 12" DIFFUSED LINEAR

MAGS Mini Series Light Fixture. The fixture engages with the track system electrically and mechanically via a magnetic connection and can be easily moved along the track. Model MAGS-ES-L30 is a DRY rated Magnetic Track, Linear Lensed Aluminum light offered in a Black or white finish. This Light Fixture is CETL listed and consumes a total of 6 watts, Diffuse Lens delivering 435 lumens using a Osram LED Module with >90 CRI. Choose 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver needed. Fixture Dimensions are 12 inches L x .89 inches W x .73 inches Deep



Model Number Configuration

MAGS-ES-L30	---	---	---
Optics	CCT	Finish	
<input type="checkbox"/> DIF - Diffuse	<input type="checkbox"/> 27 - 2700K	<input type="checkbox"/> BL - Black	
	<input type="checkbox"/> 30 - 3000K	<input type="checkbox"/> WH - White	
	<input type="checkbox"/> 35 - 3500K		
	<input type="checkbox"/> 40 - 4000K		

Electrical

Voltage	24V
Dimming	Driver dependent
Power	6W
Lumens	435
Power factor	N/A

Environmental

CRI	>90
Environment	Dry
Light Source	LED
Chip	Osram
Life rating	N/A
Listings	C-ETL Listed to UL1598

Mechanical

Installation	N/A
Cord Length	N/A
Dimensions	12 inches L x .89 inches W x .73 inches Deep
Weight	N/A
Material	Aluminum and acrylic
Finish	Powder Coated


Driver Options

Driver code	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants.
--------------------	--

Photometric and Light Distribution

DIF

Diffuse



$h(m)$	$E(lx)$	$\Phi(m)$
1	168	$\Phi 2.44$
2	42	$\Phi 4.88$
3	18	$\Phi 7.32$
4	10	$\Phi 9.76$
5	6	$\Phi 12.20$