


# MAGS MINI CONE PENDANT

MAGS Mini Series Magnetic Track, Cone Pendant Light Fixture. Choice of black or white finish. CETL listed. 6.65 inches diameter, 58 inch maximum overall height. 1 Light, 10 watt, Cree LED delivering 264 lumens. +90 CRI. 65-degree beam spread. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver, sold separately.



## Model Number Configuration

### MAGS-ES-CN

---  
**Optics**

D65 - 65°

---  
**CCT**

27 - 2700K

30 - 3000K

35 - 3500K

40 - 4000K

---  
**Finish**

BL - Black

WH - White

## Electrical

|                     |                  |
|---------------------|------------------|
| <b>Voltage</b>      | 24V              |
| <b>Dimming</b>      | Driver dependent |
| <b>Power</b>        | 10W              |
| <b>Lumens</b>       | 264              |
| <b>Power factor</b> | N/A              |

## Environmental

|                     |                        |
|---------------------|------------------------|
| <b>CRI</b>          | >90                    |
| <b>Environment</b>  | Dry                    |
| <b>Light Source</b> | LED                    |
| <b>Chip</b>         | Cree                   |
| <b>Life rating</b>  | N/A                    |
| <b>Listings</b>     | C-ETL Listed to UL1598 |

## Mechanical

|                     |  |
|---------------------|--|
| <b>Installation</b> | N/A                                    |
| <b>Cord Legth</b>   | N/A                                    |
| <b>Dimensions</b>   | 6.65" Dia x 54" maximum overall height |
| <b>Weight</b>       | N/A                                    |
| <b>Material</b>     | Aluminum                               |
| <b>Finish</b>       | Powder Coated                          |


## Driver Options

|                    |  |
|--------------------|--|
| <b>Driver code</b> | PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants. PS-60-ELV - 60W, 24V Power Supply. 120V Only with ELV Dimming to 10%. Fits in 4x4 Rectangular Junction Box. |
|--------------------|--|

**Photometric and Light Distribution**

**D65**

**Diffuse**



| h(m) | E(lx) | Φ(m)  |
|------|-------|-------|
| 1    | 333   | Φ1.24 |
| 2    | 83    | Φ2.48 |
| 3    | 37    | Φ3.72 |
| 4    | 20    | Φ4.96 |
| 5    | 13    | Φ6.20 |