


# MAGS MINI CONE PENDANT

MAGS Mini Series Magnetic Track, Cone Pendant Light Fixture. Choice of black or white finish. CETL listed. 6.65 inches diameter, 58 inch maximum overall height. 1 Light, 10 watt, Cree LED delivering 264 lumens. +90 CRI. 65-degree beam spread. Choice of 2700K, 3000K, 3500K, or 4000K CCT. Dimmable via 24V Volt Remote Driver, sold separately.



## Model Number Configuration

### MAGS-ES-CN

---  
**Optics**

D65 - 65°

---  
**CCT**

27 - 2700K

30 - 3000K

35 - 3500K

40 - 4000K

---  
**Finish**

BL - Black

WH - White

## Electrical

<b>Voltage</b>	24V
<b>Dimming</b>	Driver dependent
<b>Power</b>	10W
<b>Lumens</b>	264
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	>90
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	Cree
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	6.65" Dia x 54" maximum overall height
<b>Weight</b>	N/A
<b>Material</b>	Aluminum
<b>Finish</b>	Powder Coated


## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants. PS-60-ELV - 60W, 24V Power Supply. 120V Only with ELV Dimming to 10%. Fits in 4x4 Rectangular Junction Box.
--------------------	--

**Photometric and Light Distribution**

**D65**

**Diffuse**



h(m)	E(lx)	Φ(m)
1	333	Φ1.24
2	83	Φ2.48
3	37	Φ3.72
4	20	Φ4.96
5	13	Φ6.20