

# ELEMENTS LH-XX-30 LIGHTING ELEMENT

LH-30 Lighting Element with indirect illumination to illuminate and highlight the glass elements. Each lighting element is sloped ceiling adaptable and height adjustable. Height adjustments are in 11.75" increments. 4.6875"Diameter x 4"H. Canopy: 2"Diameter x .5"H



## Model Number Configuration

**LH-xx-30**

--

**CCT**

27 - 2700K

--

**Finish**

GO - Gold

CH - Chrome

## Electrical

<b>Voltage</b>	120-277V (UNV)
<b>Dimming</b>	N/A
<b>Power</b>	N/A
<b>Lumens</b>	150 Lumens
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	N/A
<b>Environment</b>	N/A
<b>Light Source</b>	N/A
<b>Chip</b>	N/A
<b>Life rating</b>	N/A
<b>Listings</b>	N/A

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	4.6875"Diameter x 4"H. Canopy: 2"Diameter x .5"H
<b>Weight</b>	N/A
<b>Material</b>	Metal
<b>Finish</b>	Plated

## Driver Options

<b>Driver code</b>	PS-96-24-UNI-UNI - Universal input (120-277V) and Universal dimming (ELV, TRIAC, 0-10V) 0-100% dimming. Up to 20 Small or 10 Large Pendants. PS-60-ELV - 60W, 24V Power Supply. 120V Only with ELV Dimming to 10%. Fits in 4x4 Rectangular Junction Box.
--------------------	--

## Wiring Guide

<b>18 AWG</b>	25 Feet
<b>16 AWG</b>	40Feet
<b>14 AWG</b>	60 feet