

SHAPES 2.0 X 2.0 LINEAR

Shapes 2.0x2.0 Linear is a refined linear luminaire that embodies timeless simplicity and modern versatility. Designers can tailor each fixture through choices of mounting type, size, color temperature, profile finish, acoustic treatments, and 3D-printed textured material options—all of which can be combined to achieve the exact aesthetic and functional balance required. The result is a soft, diffused glow with high visual comfort and a profile that can be visually quiet or richly expressive.

Key Features:

- Choice of surface or suspension mount
- Offered in several lengths
- 90+ CRI diffused optics
- 0–10V standard dimming (other protocols available upon request)
- CCT options: 2400K–4000K, RGB, RGBW, Tunable White
- Electrical: 100–277V universal input
- Accessories: Emergency battery backup
- Material options include: profile finishes, 3mm acoustic wrap and 3D-printed textured surfaces
- Wide array of profile finishes including powder coat, sandblast painting, anodized brushing, plating, and custom RAL
- Compatible with Shapes Linear and Circular Connectors for creating shapes and configurations
- Flicker-free illumination
- 5 year warranty

Shapes 2.0x2.0 Linear Pendant blends form, texture, and light into a highly functional yet visually compelling fixture that enhances both modern and classic interiors.

Model Number Configuration



SHP-2.0x2.0-LIN**Acrylic Length****Optics** 1970 - 19.7 in 2360 - 23.6 in 2750 - 27.5 in 3140 - 31.4 in 3540 - 35.4 in 3930 - 39.3 in 4320 - 43.2 in 4720 - 47.2 in 5110 - 51.1 in 5500 - 55 in 5900 - 59 in 6290 - 62.9 in 6680 - 66.8 in 7070 - 70.7 in 7470 - 74.7 in 7860 - 78.6 in 8250 - 82.5 in 8650 - 86.5 in 9040 - 90.4 in 9430 - 94.3 in

PROJECT NAME:

Fixture Type:

CCT

Product sheet printed on: 2026-02-21 16:32:56

Finish See Data Sheet 24 - 2400K 27 - 2700K 30 - 3000K 35 - 3500K 40-4000K RGB - RGB RGBW - RGBW TUN - Tunable White

Electrical

Voltage	120-277V
Dimming	0-10V
Power	N/A
Lumens	N/A
Power factor	N/A

Environmental

CRI	90+
Environment	Dry
Light Source	LED
Chip	N/A
Life rating	N/A
Listings	C-ETL Listed to UL1598

Mechanical

Installation	N/A
Cord Length	N/A
Dimensions	2"x2" profile
Weight	N/A
Material	Aluminum, Fabric, Polycarbonate
Finish	See following pages to select finishes

Driver Options

Driver code	N/A
--------------------	-----