

# SHAPES 2.0 X 2.0 LINEAR

Shapes 2.0x2.0 Linear is a refined linear luminaire that embodies timeless simplicity and modern versatility. Designers can tailor each fixture through choices of mounting type, size, color temperature, profile finish, acoustic treatments, and 3D-printed textured material options—all of which can be combined to achieve the exact aesthetic and functional balance required. The result is a soft, diffused glow with high visual comfort and a profile that can be visually quiet or richly expressive.

## Key Features:

- Choice of surface or suspension mount
- Offered in several lengths
- 90+ CRI diffused optics
- 0-10V standard dimming (other protocols available upon request)
- CCT options: 2400K-4000K, RGB, RGBW, Tunable White
- Electrical: 100-277V universal input
- Accessories: Emergency battery backup
- Material options include: profile finishes, 3mm acoustic wrap and 3D-printed textured surfaces
- Wide array of profile finishes including powder coat, sandblast painting, anodized brushing, plating, and custom RAL
- Compatible with Shapes Linear and Circular Connectors for creating shapes and configurations
- Flicker-free illumination
- 5 year warranty

Shapes 2.0x2.0 Linear Pendant blends form, texture, and light into a highly functional yet visually compelling fixture that enhances both modern and

classic interiors.

## Model Number Configuration



SHP-2.0x2.0-LIN

**LUXFORMAE**  
Acrylic Length

---  
**Optics**

---  
**CCT**

PROJECT NAME:

FIXTURE TYPE:

---

Product sheet printed on: 2026-06-23 17:45:52

**Finish**

1970 - 19.7 in

DF- Diffused

24 - 2400K

See Data Sheet

2360 - 23.6 in

27 - 2700K

2750 - 27.5 in

30 - 3000K

3140 - 31.4 in

35 - 3500K

3540 - 35.4 in

40-4000K

3930 - 39.3 in

RGB - RGB

4320 - 43.2 in

RGBW - RGBW

4720 - 47.2 in

TUN - Tunable White

5110 - 51.1 in

5500 - 55 in

5900 - 59 in

6290 - 62.9 in

6680 - 66.8 in

7070 - 70.7 in

7470 - 74.7 in

7860 - 78.6 in

8250 - 82.5 in

8650 - 86.5 in

9040 - 90.4 in

9430 - 94.3 in

## Electrical

<b>Voltage</b>	120-277V
<b>Dimming</b>	0-10V
<b>Power</b>	N/A
<b>Lumens</b>	N/A
<b>Power factor</b>	N/A

## Environmental

<b>CRI</b>	90+
<b>Environment</b>	Dry
<b>Light Source</b>	LED
<b>Chip</b>	N/A
<b>Life rating</b>	N/A
<b>Listings</b>	C-ETL Listed to UL1598

## Mechanical

<b>Installation</b>	N/A
<b>Cord Legth</b>	N/A
<b>Dimensions</b>	2"x2" profile
<b>Weight</b>	N/A
<b>Material</b>	Aluminum, Fabric, Polycarbonate
<b>Finish</b>	See following pages to select finishes

## Driver Options

<b>Driver code</b>	N/A
--------------------	-----