PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on: **2025-10-08 16:14:04**

SHAPES FORM 360

Surface, Suspension, Recessed

Form 360 is a versatile family of low-profile circular luminaires available as surface, suspension or recessed mount. With multiple diameters, depths, finishes, and control options, the collection delivers uniform, flicker-free illumination ideal for commercial, hospitality, and architectural environments. Its flexible specification options make it easy to integrate Form 360 into a wide range of ceiling conditions and design intents.

Key Features

- Size Range: Standard diameters from 13″– 47.2″
- Flexible Ordering: No minimum order quantity — single fixtures available
- High Performance: 100 lm/W, 90+ CRI
- Mounting Options: Suspension or surface
- Driver Options: Built-in driver or remote ceiling box
- Light Quality: Uniform, flicker-free illumination
- Durability: 5-year warranty
- Finishes: White, Black, Silver, Gold, or Custom RAL
- Electrical: 100–277V universal input
- Control Options: 0–10V, Tunable White
- Accessories: Emergency battery backup
- Ease of Installation: Streamlined, contractor-friendly setup

Model Number Configuration

SHP-FORM 360

__ Mounting	__ Height	____ Size	__ Dimming	__ Accessories	__ CCT	__ Finish
☐ PT- Pendant	☐ S - 2.36 in	☐ 1300 - 13 in	☐ 02- 0-10V	☐ EM- Emergency	☐ 27 - 2700K	☐ Black
☐ SF- Surface	☐ M - 3.15 in	☐ 1460 - 14.6 in			☐ 30 - 3000K	☐ White
☐ RC- Recessed	☐ T- 3.93 in	☐ 2050 - 20.5 in			☐ 35 - 3500K	☐ Silver
		☐ 2130 - 21.3 in			☐ 40-4000K	☐ Gold
		☐ 2600 - 26 in			☐ RGB - RGB	☐ Custom RAL
		☐ 3070 - 30.7 in			☐ RGBW - RGBW	
		☐ 3230 - 32.3 in			☐ TUN - Tunable White	
		☐ 3700 - 37 in				
		☐ 4720 - 47.2 in				

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2024 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.

PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on: **2025-10-08 16:14:04**

Electrical

Voltage	120-277V
Dimming	0-10V, Tunable white
Power & Lumens	13 in - 15W, 1500 Lumens 14.6 in - 20W, 2000 Lumens 20.5 in - 35W, 3500 Lumens 21.3 in - 40W, 4000 Lumens 26 in - 60W, 6000 Lumens 30.7 in - 80W, 8000 Lumens 32.3 in - 90W, 9000 Lumens 37 in - 120W, 12000 Lumens 47.2 in - 200W, 20000 Lumens
Accessories	Emergency battery backup
Power factor	N/A

Driver Options

Driver code	N/A

Environmental

CRI	90+
Environment	Dry
Light Source	LED
Chip	N/A
Life rating	N/A
Listings	C-ETL Listed to UL1598

Mechanical

Installation	N/A
Cord Legth	10Ft for pendants
Dimensions	2.36” / 3.15“ / 3.93” Height/Depth 13” / 14.6” / 20.5” / 21.3” / 26” / 30.7” / 32.3” / 37” / 47.2” Diameters
Weight	N/A
Material	Aluminum, Fabric, Polycarbonate
Finish	Black, White, Silver or Gold
Optics	Polycarbonate diffusion panel
Distribution	Direct (down light)

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2024 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.

Notes

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2024 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.