PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on:

FORM 360-IK10 | Recessed and Grid Mount SCA26RC

Form 360-IK10 Recessed and Grid Mount is a low-profile circular LED luminaire designed for seamless integration into architectural ceiling systems. Combining a painted aluminum housing and frame with an impact-resistant opal polycarbonate diffuser, the fixture delivers uniform, flicker-free illumination with a clean, contemporary appearance.




Available in five diameters with multiple lumen output options, Form 360-IK10 Recessed and Grid Mount offers flexible installation in drywall, wood, metal, and suspended grid ceilings. Ideal for commercial, corporate, educational, and healthcare environments where durability, visual comfort, and clean ceiling integration are essential.

Construction: Housing and frame: Painted Aluminum
Finish: White, black, or custom RAL colors
Diffuser: Impact-resistant opal polycarbonate

Diffuser retention system:
Mechanically secured aluminum retaining ring with screws

Performance:
- Multiple lumen output packages available per size
- 90+ CRI
- 3000K, 3500K, or 4000K
- Universal voltage input: 120–277V
- 0–10V dimming
- Uniform, flicker-free illumination

Mounting Options:
- Recessed mounting for drywall, wood, or metal ceilings
- Grid mounting for suspended T-bar ceiling systems
- Cable mounting for drop ceiling applications



Warranty
5-year limited warranty

SCA26RC-

__	____	__	___	__	__	__	____
Mounting	**Size**	**Optics**	**Output**	**Driver**	**Accessories**	**CCT**	**Profile Finish**

__	____	__	___
Mounting PT- Cable Mount for Drop Ceiling RC- Recessed- Drywall/Wood/Metal GM- Grid Mounting for Drop Ceiling	**Size** 300- 13" Fixture Body 600- 26" Fixture Body 900- 37" Fixture Body 1200- 47" Fixture Body 1500- 60" Fixture Body	**Optics** DF- Diffused	**Output** LO- Low Output MO- Medium Output HO- High Output XLO- Extra Low Output (60" only)

__	__	__	_____
Driver RT- Remote IN- Integral	**Accessories** EM- Emergency	**CCT** 30- 3000K 35- 3500K 40- 4000K	**Profile Finish** WHITE- Painted White BLACK- Painted Black CUSTOM- Painted Custom RAL

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2026 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.


PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on:


Mounting

PT – Cable Mount (Drop Ceiling)
Suspended cable mounting system designed for installation below drop ceiling conditions. Adjustable aircraft cables provide stable support and allow for field-adjustable suspension height.




13" - 13.5"Ceiling Tile Cutout
26" - 26.5" Ceiling Tile Cutout
37" - 37.5" Ceiling Tile Cutout
47" - 47.5" Ceiling tile Cutout
60" - 60.5" Ceiling tile Cutout

RC – Recessed (Drywall / Wood / Metal Ceilings)
Recessed mounting configuration suitable for drywall, wood, or metal ceiling applications. Fixture secured using dedicated recessed mounting brackets for clean ceiling integration.



13" - 13.5"Ceiling Tile Cutout
26" - 26.5" Ceiling Tile Cutout
37" - 37.5" Ceiling Tile Cutout
47" - 47.5" Ceiling tile Cutout
60" - 60.5" Ceiling tile Cutout

GM – Grid Mount (Drop Ceiling)
Designed for installation within standard T-bar grid ceiling systems. Fixture integrates directly into grid structure for secure, flush alignment within lay-in ceiling applications.



13" - 13.5"Ceiling Tile Cutout
26" - 26.5" Ceiling Tile Cutout
37" - 37.5" Ceiling Tile Cutout
47" - 47.5" Ceiling tile Cutout
60" - 60.5" Ceiling tile Cutout

Output

Integral LED - 90+ CRI, 3000K, 3500K or 4000K CCT

	Size	Output Type	Power	Lumens	CCmA
INTEGRAL DRIVER	13"	Low Output	-	-	-
		Medium Output	-	-	-
		High Output	20W	1800	500mA
	26"	Low Output	40W	3600	500mA
		Medium Output	60W	5400	1500mA
		High Output	-		
	37"	Low Output	80W	7200	1000mA
		Medium Output	120W	10800	1500mA
		High Output	160W	14400	1000mA
	47"	Low Output	120 W	10800	750mA
		Medium Output	200 W	18000	1250mA
		High Output	240 W	21600	1250mA
	60"	Extra Low Output	-	-	-
		Low Output	200 W	18000	1250mA
		Medium Output	240 W	21600	750mA
		High Output	360 W	32400	1200mA

	Size	Output Type	Power	Lumens	CCmA
REMOTE DRIVER	13"	Low Output	-	-	-
		Medium Output	10W	900	-
		High Output	20W	1800	500mA
	26"	Low Output	42W	3780	1050mA
		Medium Output	60W	5400	1050mA
		High Output	78W	7020	2000mA
	37"	Low Output	84W	7560	2100mA
		Medium Output	120W	10800	2100mA
		High Output	156W	14040	3900mA
	47"	Low Output	140W	12600	3500mA
		Medium Output	200 W	18000	5000mA
		High Output	260W	23400	3250mA
	60"	Extra Low Output	70W	6300	1050mA
		Low Output	200 W	18000	5000mA
		Medium Output	280W	25200	3500mA
		High Output	360 W	32400	4500mA

Driver Type

INTEGRAL


- 0-10V Dimming
- 120V-277V (UNV)
- 0% Minimum Dimming Level
- Electronic Driver
- Power Factor ≥0.9
- THD ≤20%
- Field Replaceable

REMOTE

- 0-10V Dimming
- 120V-277V (UNV)
- 1% Minimum Dimming Level
- Electronic Driver
- Power Factor ≥0.97 @115V
  ≥0.92 @277VAC
- THD ≤10%
- Field Replaceable

Optic Type

DF- Polycarbonate diffuse diffuser.
Diffuser secured with retaining ring and screws



Accessories

Emergency with battery back up.

- 90 Minute Battery Duration
- 8 or 15W
- Self Testing

Certifications

Impact Resistance Rating
13" - IK10
26" - IK10
37" - IK10
47" - IK10
60" - IK7

Profile Color

Powder coated - White
Powder coated - Black
Powder coated - Custom RAL

 - Copyright 2026 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.


PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on:


Recessed - Installation

1




First, fix the box with screws.

2




Second, make a hole by the size of the luminaire

3a If the driver is dimming & external installation




Connect the wires correctly as above showing.

3b If the driver is non-dimming & external installation




Connect the wires correctly as above showing.

4




Install the lamp with the screws.

5



Install ceiling finishing gasket around the rim of the ceiling opening.

6



Finished

LuxFormae Corp. | New York, NY 10018, USA | www.luxformae.com | sales@luxformae.com - Copyright 2026 LuxFormae Corp. Pictures, descriptions and technical data have to be considered as purely indicative. While maintaining the basic characteristics of the product, the manufacturer reserves the right to make modifications at any time with the sole aim of improvement.

PROJECT NAME:

FIXTURE TYPE:

Product sheet printed on:

Grid Mount - Installation

